

WAAS CH 82134 W26A	APP CRS 258°	Rwy Idg 5000 TDZE 209 Apt Elev 239
--	------------------------	---

RNAV (GPS) RWY 26


CHERAW MUNI/LYNCH BELLINGER FLD (CQW)

T setting and increase all DA 44 feet, all MDA 60 feet, LNAV/VNAV all Cats visibility $\frac{1}{8}$ mile, LNAV/VNAV Cat C/D and Circling Cat C/D visibility $\frac{1}{4}$ mile. Helicopter visibility reduction below 1 SM NA.

A For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 54°C (130°F). Procedure NA at night.

MISSED APPROACH:
Climb to 2500 direct
YOYUL and hold.

AWOS-3 124.825	FLORENCE APP CON ★ 118.6 341.7	UNICOM 122.8 (CTAF) ①
--------------------------	--	---------------------------------



CATEGORY	A	B	C	D
LPV DA		459-1	250 (300-1)	
LNAV/VNAV DA		578-1¼	369 (400-1¼)	
LNAV MDA		560-1	351 (400-1)	
C CIRCLING	700-1 461 (500-1)		1060-2½ 821 (900-2½)	1060-2¾ 821 (900-2¾)

REIL Rwy's 8 and 26 **L**
MIRL Rwy 8-26 **L**