

APP CRS

Rwy Idg

269°

3180

TDZE

9

Apt Elev

9

RNAV (GPS) RWY 28R

NORTH PERRY (HWO)

RNP APCH. RADAR required for procedure entry.

▼

Rwy 28R helicopter visibility reduction below ¾ SM NA. Straight-in minimums NA at night. Circling Rwy 1R, 10L, 19L, 28R NA at night. Circling NA for Cat C south of Rwy 10R-28L.

MISSED APPROACH:

Climb to 2000 direct FRDND and hold.

ATIS	MIAMI APP CON	NORTH PERRY TOWER*	GND CON	UNICOM
135.475	128.6 306.975	132.1 (CTAF) 0 254.3	120.45 254.3	122.95

ELEV	9	D	TDZE	9
------	---	---	------	---

2000	FRRDY	VGSI and descent angles not coincident (VGSI Angle 3.50/TCH 39).	CUDES	
JUMUV	CIBIB	1700	2000	
269°	275°	3.00° TCH 43		
0.3	4.9 NM	5.3 NM		
CATEGORY	A	B	C	D
LNAV MDA	520-1	511 (600-1)	520-1 5/8 511 (600-1 3/8)	NA
CIRCLING	560-1	551 (600-1)	560-1 1/2 551 (600-1 1/2)	NA

HOLLYWOOD, FLORIDA

Orig-D 19MAY22

26°00'N-80°14'W

NORTH PERRY (HWO)

RNAV (GPS) RWY 28R