

APP CRS
108°

Rwy Idg
5001

TDZE
790

Apt Elev
790

RNAV (GPS) RWY 11

FULTON COUNTY (R/C/R)

T

A

DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Goshen altimeter setting: increase all MDA 100 feet and visibility LNAV Cats C and D and Circling Cats C and D ¼ SM.

MISSED APPROACH: Climb to 3000 direct LOWTO and hold.

AWOS-3
118.775

SOUTH BEND APP CON ★
132.05 257.8

UNICOM
122.7 (CTAF) 0

The main chart displays the RNAV (GPS) RWY 11 approach. Key features include:

- Waypoints:** KOMECE (IF/IAF), LIMEY (IAF), AFAGU (FAF), VOYUP (2.4 NM to RW11), and ISOSY (IAF).
- Altitudes:** 3000 ft at KOMECE, 2500 ft at AFAGU, and 1600 ft at VOYUP.
- Angles:** 108° and 288° for the main approach; 198° and 018° for the holding pattern.
- Holding Pattern:** 4 NM holding pattern at KOMECE.
- LOWTO:** 4 NM Low Altitude Terminal Obstacle (LOWTO) diagram showing the approach path and obstacles.

4 NM Holding Pattern

VGSI and descent angles not coincident (VGSI Angle 3.50/TCH 50).

3000 LOWTO

108° 288° 108° 108°

2500 1600

3.05° TCH 45

VOYUP 2.4 NM to RW11

RW11

6.1 NM 2.8 NM 2.4 NM

CATEGORY	A	B	C	D
LNAV MDA	1220-1	430 (500-1)	1220-1¼ 430 (500-1¼)	1220-1½ 430 (500-1½)
CIRCLING	1280-1 490 (500-1)	1360-1 570 (600-1)	1480-2 690 (700-2)	1620-2¾ 830 (900-2¾)

REIL Rwy 11 and 29 0

MIRL Rwy 11-29 0

ROCHESTER, INDIANA

Amtd 1A 02DEC21

41°04'N-86°11'W

FULTON COUNTY (R/C/R)

RNAV (GPS) RWY 11