

WAAS  
CH **93528**  
**W36A**

APP CRS  
**359°**

Rwy Idg  
TDZE **343**

Apt Elev  
**343**

**RNAV (GPS) RWY 36**

NACOGDOCHES A L MANGHAM JR RGNL (OCH)

RNP APCH-GPS.  
Baro-VNAV NA when using Lufkin altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 34°C. When local altimeter setting not received, use Lufkin altimeter setting: increase LPV DA to 599 feet, LNAV/VNAV DA to 681 feet, and visibility LNAV/VNAV all Cats ½ SM, increase all MDA 60 feet and visibility LNAV Cat C ½ SM and Circling Cat C ½ SM.

MALSR  
MISSED APPROACH: Climb to 2400 direct XOWNU and on track 352° to DRBOB and hold.

AWOS-3PT  
**135.625**

HOUSTON CENTER  
**125.175 285.575**

UNICOM  
**123.0 (CTAF)**

MISSED APCH FIX

4 NM Holding Pattern

CATEGORY	A	B	C	D
LPV DA	543-½ 200 (200-½)			NA
LNAV/VNAV DA	625-½ 282 (300-½)			NA
LNAV MDA	700-½ 357 (400-½)	700-⅝ 357 (400-⅝)		NA
CIRCLING	860-1 517 (600-1)	1080-2 737 (800-2)		NA

ELEV 343

TDZE 343