RNAV (GPS) RWY 20

CENTERVILLE MUNI (GHM)

WAAS	APP CRS	Rwy Idg	3763
CH 48838	201°	TDZE	765
W20A		Apt Elev	765

Obtain local altimeter setting on CTAF, when not received, use Columbia/Mount Pleasant altimeter setting and increase all MDA 80 feet. Increase LP Cats C and D visibility ¼ mile; LNAV Cats C and D ⅛ mile; Circling Cat D ¼ mile. DME/DME RNP-0.3 NA. Procedure NA at night. Helicopter visibility reduction below 1 SM NA.

NA

MISSED APPROACH: Climb to 3000 direct WOGUT and hold.

MEMPHIS CENTER	UNICOM
125.85 379.25	122.8 (CTAF) L



CATEGORY	A	B	C	D
LP MDA	1160-1 395 (400-1)		1160-1⅛ 395 (400-1⅛)	
LNAV MDA	1220-1 455 (500-1)		1220-1⅜ 455 (500-1⅜)	
C CIRCLING	1260-1 495 (500-1)		1280-1½ 515 (600-1½)	1520-2½ 755 (800-2½)

SE-1, 10 JUL 2025 to 07 AUG 2025
SE-1, 10 JUL 2025 to 07 AUG 2025