




WAAS CH 42820 W08A	APP CRS 077°	Rwy Idg TDZE Apt Elev	7723 1274 1277
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 8
CENTRAL WISCONSIN (CWA)

RNP APCH - GPS.			MALSR 	MISSED APPROACH: Climb to 3000 direct ASARE and hold.	
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. For inop ALS, increase LNAV Cat C and D visibility to 1½ SM.					
ATIS 127.45	MINNEAPOLIS CENTER 124.4 317.7	CWA TOWER ★ 119.75 (CTAF) 0 360.7		GND CON 121.9 360.7	UNICOM 122.95



4 NM Holding Pattern		TUCYU	HENPA	3000	WOKOS	1.7 NM to RW08	ASARE
6000 ← 257°		3000 → 077°	3000	1860	1.1 NM to RW08		
GP 3.00°		TCH 55	7.6 NM	3.6 NM	0.6 NM	1.1 NM	
CATEGORY	A	B	C	D			
LPV DA	1474-½		200 (200-½)				
LNAV/VNAV DA	1601-½		327 (400-½)				
LNAV MDA	1640-½	366 (400-½)	1640-¾		366 (400-¾)		
CIRCLING	1740-1	463 (500-1)	1740-1½		1840-2		
			463 (500-1½)		563 (600-2)		



EC-3, 10 JUL 2025 to 07 AUG 2025

EC-3, 10 JUL 2025 to 07 AUG 2025