



WAAS CH 66002 W05A	APP CRS 053°	Rwy Idg TDZE 683 Apt Elev 683	7001
--	------------------------	---	-------------

RNAV (GPS) RWY 5

CHARLOTTE/MONROE EXEC (EQY)

RNP APCH-GPS.		MALSR	MISSED APPROACH: Climb to 1140 then climbing right turn to 2500 direct MOSEE and hold.
Rwy 5 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C or above 54°C. Inop table does not apply to LPV all Cats. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM and LNAV all Cats visibility to 1 SM.			

ASOS 135.775	CHARLOTTE APP CON 120.05 307.8	CLNC DEL 132.55	UNICOM 122.7 (CTAF) 0
------------------------	--	---------------------------	---------------------------------



FATED		JAMUN	WUVUL	MOSEE
2500		2500	1.6 NM to RWY 5	1140
2500		2500	0.9 NM to RWY 5	2500
GP 3.00°		1220	0.7 NM	MOSEE
TCH 46		1220	0.9 NM	
8 NM		4 NM	0.7 NM	0.9 NM
CATEGORY	A	B	C	D
LPV DA	933-¾ 250 (300-¾)			
LNAV/VNAV DA	1001-¾ 318 (400-¾)			
LNAV MDA	1020-¾ 337 (400-¾)			
CIRCLING	1220-1	537 (600-1)	1220-1½	1480-2½
			537 (600-1½)	797 (800-2½)