

WAAS

CH 70426

W33A

APP CRS

329°

Rwy Idg

5000

TDZE

336

Apt Elev

336

RNAV (GPS) RWY 33

WARRENTON/FAUQUIER (HWY)

▼

⚠

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Culpeper altimeter setting; increase all MDA 40 feet, increase LP Cat C/D visibility ½ SM, increase LNAV Cat C/D and Circling Cat D visibility ¼ SM.

MISSED APPROACH: Climb to 800 then climbing left turn to 3000 direct CSN VORTAC and hold, continue climb in hold to 3000.

AWOS-3 120.35	CJR AWOS-3 119.325	POTOMAC APP CON 128.525 306.925	UNICOM 122.7 (CTAF) 0
------------------	-----------------------	------------------------------------	--------------------------

RADAR REQUIRED

WASHINGTON DC METROPOLITAN SFRA

WARNING -- WASHINGTON DC SFRA. CONTACT POTOMAC APP CON

△ 1048

CASANOVA CSN

4 NM

207°

207°

358

RW33

476

469

329°

LRGNT 2.5 NM to RW33

(FAF) CRLYN

2000

335°

6.5 NM

(IF/IAF) ANTNY

145°

325°

4 NM

DEMO 1 MOA

NoPT for arrival at ANTNY on V286 northwest bound.

MSA RW33 25 NM

4700

ELEV 336

TDZE 336

☆ 370 ±

0.5% UP

5000 X 100

33

329°

Procedure NA when DEMO 1 MOA active.

800

3000

CSN

4 NM Holding Pattern

CRLYN

ANTNY

145°

335°

325°

2000

1.1 NM

1.4 NM

2.6 NM

6.5 NM

1.1 NM to RW33

LRGNT 2.5 NM to RW33

1160

329°

3.00°

TCH 45

CATEGORY	A	B	C	D
LP MDA	720-1 384 (400-1)		720-1½ 384 (400-1½)	
LNAV MDA	740-1 404 (500-1)		740-1½ 404 (500-1½)	
CIRCLING	760-1 424 (500-1)	800-1 464 (500-1)	880-1½ 544 (600-1½)	980-2 644 (700-2)

WARRENTON, VIRGINIA

Orig-B 15JUL21

WARRENTON/FAUQUIER (HWY)

RNAV (GPS) RWY 33

38°35'N-77°43'W