

WAAS CH 61016 W23A	APP CRS 229°	Rwy Idg TDZE Apt Elev	6002 101 101
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 23

LOWCOUNTRY RGNL (RBW)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Charleston AFB/Intl altimeter setting. DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. For inop ODALS, increase LNAV/VNAV all Cats visibility to 1¼ mile and LNAV Cat D visibility to 1½ mile. When local altimeter setting not received, use Charleston AFB/Intl altimeter setting; increase LPV DA to 379 feet and LNAV/VNAV DA to 542 feet and all MDA 80 feet; increase LNAV/VNAV visibility all Cats, LNAV Cats C/D visibility, and Circling Cat D visibility ¼ mile; increase Circling Cat C visibility ½ mile. For inop ODALS when using Charleston AFB/Intl altimeter setting, increase LPV all Cats visibility to ¾ mile and LNAV/VNAV all Cats and LNAV Cats C/D visibility to 1½ mile.

ODALS

MISSED APPROACH: Climb to 1200 then climbing right turn to 2100 direct LAMKE and hold.

AWOS-3PT 118.725	CHARLESTON APP CON 120.7 306.925	UNICOM 122.8 (CTAF)
----------------------------	--	-------------------------------

ELEV 101 TDZE 101

REIL Rwy 23
MIRL Rwy 5-23

1200 2100 LAMKE VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 46). LAMKE 4 NM Holding Pattern				
* LNAV only				
* 1.3 NM to RW23				
DOTMY 1800 229° 1800 049° 2100 GP 3.00° TCH 43				
1.3 3.9 NM 6.3 NM				
CATEGORY	A	B	C	D
LPV DA	301-¾		200 (200-¾)	
LNAV/VNAV DA	464-1½		363 (400-1½)	
LNAV MDA	560-¾	459 (500-¾)	560-1½	459 (500-1½)
CIRCLING	620-1 519 (600-1)	640-1 539 (600-1)	700-1½ 599 (600-1½)	700-2 599 (600-2)

WALTERBORO, SOUTH CAROLINA
Amdt 2 03MAR16

32°55'N-80°38'W

LOWCOUNTRY RGNL (RBW)
RNAV (GPS) RWY 23