

WAAS CH 45507 W15A	APP CRS 153°	Rwy Idg TDZE Apt Elev 6001 82 82
--	------------------------	--

RNAV (GPS) RWY 15

KISSIMMEE GATEWAY (ISM)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). DME/DME RNP-0.3 NA. VDP and Baro-VNAV NA when using Orlando Intl altimeter setting. Inoperative table does not apply to LNAV/VNAV all Cats and LNAV Cat C. When local altimeter setting not received, use Orlando Intl altimeter setting and increase LPV DA all Cats to 309, LNAV/VNAV DA all Cats to 559, and all MDA 40 feet; increase LNAV/VNAV all Cats and Circling Cat C visibility ¼ mile.

MALSF

MISSED APPROACH: Climb to 2200 direct YARTU and on track 221° to TEMPE and hold

ATIS 128.775	ORLANDO APP CON 119.4 351.9	KISSIMMEE TOWER ★ 124.45 (CTAF)	CLNC DEL 121.7	CLNC DEL 123.95 (when twr closed)	GND CON 121.7	UNICOM 122.95
------------------------	---------------------------------------	---	--------------------------	--	-------------------------	-------------------------

Procedure NA for arrivals at ORL VORTAC on V533 northeast bound.

Procedure NA for arrivals at JENSN on V152 southwest bound.

MISSED APCH FIX

4 NM

205°

025°

1133 A

2200 YARTU tr 221° TEMPE

*1.2 NM to RW15

*LNAV only.

MSA RW15 25 NM

3000

WERPO		WADSI		YARTU		TEMPE			
2000		1200		2200		tr 221°			
Procedure Turn NA									
GP 3.00°									
TCH 51									
6.1 NM		2.1 NM		1.2					
CATEGORY	A	B	C	D					
LPV DA	282-¾		200 (200-¾)						
LNAV/VNAV DA	532-1½		450 (500-1½)						
LNAV MDA	520-¾	438 (500-¾)	520-1¼	520-1½	438 (500-1¼)	438 (500-1½)			
CIRCLING	680-1	598 (600-1)	680-1½	700-2	598 (600-1½)	618 (700-2)			

ELEV 82

TDZE 82

REIL Rwy 6, 24 and 33

MIRL Rwy 15-33 and 6-24

ORLANDO, FLORIDA

Amdt 1A 19MAY22

28°17'N-81°26'W

KISSIMMEE GATEWAY (ISM)

RNAV (GPS) RWY 15