RNAV (GPS) RWY 22

CULPEPER RGNL (CJR)

WAAS	APP CRS	Rwy Idg	5000
CH 56306	218°	TDZE	315
W22A		Apt Elev	316

RNP APCH - GPS.

Rwy 22 helicopter visibility reduction below 1 SM NA. Baro-VNAV NA when using IAD altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C. When local altimeter setting not received, use IAD altimeter setting and increase LPV DA to 730 feet; increase LNAV/VNAV DA to 776 feet; increase all MDAs 80 feet and visibility Cats C ¼ SM and D ⅛ SM. Straight-in Rwy 22 at night, Circling Rwy 4, 22 at night, operational VGSI required, remain on or above VGSI glidepath until threshold.

MISSED APPROACH: Climb to 3000 direct FAXIK and hold.

AWOS-3	POTOMAC APP CON	CLNC DEL	UNICOM
119.325	128.525 306.925	121.6	123.075 (CTAF) L



CATEGORY	A	B	C	D
LPV DA	657-1¼ 342 (400-1¼)			
LNAV/VNAV DA	703-1½ 388 (400-1½)			
LNAV MDA	800-1 485 (500-1)		800-1¼ 485 (500-1¼)	800-1½ 485 (500-1½)

NE-3, 10 JUL 2025 to 07 AUG 2025
NE-3, 10 JUL 2025 to 07 AUG 2025