

APP CRS  
**188°**

Rwy Idg  
TDZE  
Apt Elev

**3501**  
**1204**  
**1207**

**RNAV (GPS) RWY 19**

ASHLAND COUNTY (3G4)

RNP APCH.

▼

NA

Rwy 19 helicopter visibility reduction below 1 SM NA.  
Procedure NA at night. Use Mansfield altimeter setting,  
when not received use Wooster altimeter setting.

MFD ASOS  
**125.3**

CLEVELAND APP CON ★  
**128.35 360.65**

UNICOM  
**122.7 (CTAF)**

ELEV 1207

TDZE 1204

188°

61

0.5% UP

3501 X 7.5

1

3000

HINPO

tr 098°

READS

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 20).

4 NM Holding Pattern

JUKAP

3.04° TCH 40

188°

008°

3000

2800

4.9 NM

6.1 NM

CATEGORY	A	B	C	D
LNAV MDA	1600-1	396 (400-1)	1600-1 <sup>1</sup> / <sub>8</sub> 396 (400-1 <sup>1</sup> / <sub>8</sub> )	NA
CIRCLING	1660-1	453 (500-1)	1740-1 <sup>1</sup> / <sub>2</sub> 533 (600-1 <sup>1</sup> / <sub>2</sub> )	NA

REIL Rws 1 and 19

MIRL Rwy 1-19

ASHLAND, OHIO

Orig-F 09SEP21

40°54'N-82°15'W

ASHLAND COUNTY (3G4)

**RNAV (GPS) RWY 19**