

24193

RNAV (GPS) RWY 36  
JONESBORO (F88)

**MISSED APPROACH:** Climb to 2400 direct FIMUG and hold.

CTAF  
122.9 **L**

81

TDZE 256

8

(2)

204:

75

©



1

10

24

Diagram illustrating the FAF-PUYOC system. The system is shown as a vertical axis with various components and distances. Key components and distances include:

- $\Delta^{752}$  and  $\Delta^{573}$  at the top.
- $\Delta_{415}$  and distances  $389 \pm$  and  $369 \pm$  near RW36.
- CIGED 1.5 NM to RW36.
- (FAF) PUYOC.
- 2000 358 (s).
- (IF/IAF) ZOBTA with a 358 distance.
- HOLD with 6000 and 2000 distances.
- A curved arrow indicates a  $178^\circ$  angle and a 4 NM distance.

2400	FIMUG
	

CATEGORY	A	B	C	D
LP MDA	620-1 364 (400-1)			NA
LNAV MDA	640-1 384 (400-1)	640-1 $\frac{1}{8}$ 384 (400-1 $\frac{1}{8}$ )		NA
CIRCLING	780-1 524 (600-1)	880-1 $\frac{3}{4}$ 624 (700-1 $\frac{3}{4}$ )		NA

JONESBORO (F88)

RNAV (GPS) RWY 36

SC-4, 10 JUL 2025 to 07 AUG 2025