

PEARLAND RGNL (LVJ)

TAKEOFF MINIMUMS
Rwys 14, 32: Standard with minimum climb of 500'/NM to 560.

TAKEOFF MINIMUMS

Rwys 14, 32: Standard with minimum climb of 500'/NM to 560.

Figure 1 is a network diagram showing the connections between various stations. The diagram includes stations like CRGR, PSTUR, PUFER, ZUUU, BORR, DILR, BOCK, MNUR, HAYY, FOWL, MARCS, WAIN, WEED, and SAN ANTONIO SAT. Each station is represented by a symbol (diamond, triangle, or circle) and is connected to other stations by lines. Each line is labeled with a distance (e.g., 12000, 2790) and a number in parentheses (e.g., (33), (34)). A north arrow is shown in the top right corner, and a scale bar (0 to 1600) is in the top left corner.

NOTE: CRGR-TRANSITION ATC assigned only
for aircraft departing 54T, AXH, EFD, GLS,
HPY, IWS, LBX, LVJ, SGR, TME, T00, T41.

(CONTINUED ON FOLLOWING PAGE)

SC-5, 10 JUL 2025 to 07 AUG 2025

NOTE: Chart not to scale.

TOP ALTITUDE: ASSIGNED BY ATC

SC-5, 10 JUL 2025 to 07 AUG 2025