

WAAS
CH **58319**
W34A

APP CRS
344°

Rwy Idg
TDZE
Apt Elev

6000
100
100

RNAV (GPS) RWY 34

YOLO COUNTY (DWA)

RNP APCH.

When local altimeter setting not received, use Travis AFB altimeter setting and increase all DA 50 feet and all MDA 60 feet, and increase LPV visibility all Cats ¼ mile, LNAV/VNAV visibility all Cats ¼ mile, and LNAV Cat C and D visibility ¼ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 42°C (107°F). Baro-VNAV NA when using Travis AFB altimeter setting.

MISSED APPROACH: Climb to 3000 direct GHEER and hold.

AWOS-3P
125.775

TRAVIS APP CON
126.6 281.45

UNICOM
123.0 (CTAF)

ELEV 100

TDZE 100

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 40).				3000	GHEER
TRIMM				*LNAV only	
PROAP				DOWNS 1.6 NM to RW34	
GP 3.00° TCH 58				RW34	
4000				*660	
2300					
6.6 NM				5.1 NM	
CATEGORY				1.6 NM	
LPV DA				A B C D	
LNAV/VNAV DA				415-1 315 (400-1)	
LNAV MDA				425-1 325 (400-1)	
				500-1 400 (400-1)	
				500-1½ 400 (400-1½)	

DAVIS/WOODLAND/WINTERS, CALIFORNIA

Amdt 2C 15AUG19

38°35'N-121°51'W

YOLO COUNTY (DWA)

RNAV (GPS) RWY 34