

WAAS CH <b>61316</b> <b>W19A</b>	APP CRS <b>188°</b>	Rwy Idg TDZE <b>961</b> Apt Elev <b>969</b>
--	------------------------	---

RNAV (GPS) RWY 19  
LAFAYETTE MUNI (3M7)

RNP APCH - GPS

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 46°C.  
▲ NA Obtain local altimeter setting on CTAF; when not received, use Bowling Green altimeter setting: increase LPV DA to 1344 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 1502 feet and all visibilities ½ SM; increase all MDAs 140 feet and visibility LNAV Cat C ¼ SM, Cat D ½ SM, and Circling Cat C and D ½ SM. Rwy 19 helicopter visibility reduction below 1 SM NA.

MISSED APPROACH:  
Climb to 3000 direct  
HETAP and hold.

NASHVILLE APP CON  
**118.4 360.7**

UNICOM  
**122.8 (CTAF)**

MSA RW19 25 NM

3100



(IAF) FUPU  
2900 NoPT  
188° (6.6)

▲ 1430

4 NM  
008°  
188°  
(IF/IAF) OZESI

2500  
188°  
(6.1)

(FAF) QALAY

1129 OLLOW  
1.8 NM to  
RW19

1140 ▲

1099 ±

▲

▲ 1342

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲

1132 ±

▲