

|  |                        |                             |   |
|--|------------------------|-----------------------------|---|
| WAAS<br>CH <b>78325</b><br><b>W02A</b> | APP CRS<br><b>018°</b> | Rwy Idg<br>TDZE<br>Apt Elev | <b>6001</b><br><b>484</b><br><b>501</b> |
|--|------------------------|-----------------------------|---|

RNAV (GPS) RWY 2

JOHN C TUNE (JWN)

▽

▲ NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Circling NA E of Rwy 2-20. Baro-VNAV and VDP NA when using Nashville Intl altimeter setting. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Nashville Intl altimeter setting and increase all DAs 39 feet and all MDAs 40 feet; increase LPV visibility all Cats ⅓ SM, LNAV visibility Cat B ¼ SM.

MISSED APPROACH:  
Climb to 3000 direct BICOL and hold.

|                        |  |   |                         |                          |  |                        |
|------------------------|--|---|-------------------------|--------------------------|--|------------------------|
| ATIS<br><b>127.075</b> | NASHVILLE APP CON<br><b>119.35 372.0</b> | JOHN TUNE TOWER ★<br><b>119.45 (CTAF) 0</b> | GND CON<br><b>121.7</b> | CLNC DEL<br><b>121.7</b> | CLNC DEL<br><b>124.55</b><br>(when twr closed) | UNICOM<br><b>122.7</b> |
|------------------------|--|---|-------------------------|--------------------------|--|------------------------|

