

| | | | |
|--|------------------------|-----------------------------|---|
| WAAS CH 99644 W18A | APP CRS 180° | Rwy Idg TDZE Apt Elev | 6001 1316 1316 |
|--|------------------------|-----------------------------|---|

RNAV (GPS) RWY 18

MONETT RGNL (HFJ)

RNP APCH - GPS.

Baro-VNAV and VDP NA when using Joplin altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Joplin altimeter setting; increase LPV DA to 1678 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 1742 feet and all visibilities ⅓ SM; increase all MDAs 120 feet and LNAV visibility Cat C/D ½ SM, and Circling visibility Cat C/D ½ SM.

MISSED APPROACH: Climb to 3100 direct STERL and hold.

| | | | |
|--------------------------|--|---------------------------|--|
| AWOS-3 118.275 | SPRINGFIELD APP CON 124.95 318.2 | CLNC DEL 121.85 | UNICOM 123.075 (CTAF) 1 |
|--------------------------|--|---------------------------|--|

ELEV 1316 TDZE 1316

180°

81

6001 X 100

0.3% UP

36

HIRL Rwy 18-36 **1**

REIL Rwy 18 **1**

| | | | | |
|----------------------|-----------------------|-----------------------|-------------------------|-------------------------|
| 3100 | STERL | SOFWR | PHENM | 4 NM Holding Pattern |
| KNOXX 1.9 NM to RW18 | 1.1 NM to RW18 | 1960 | 3000 | 360° 4000 180° 3000 |
| 1.1 NM | 0.8 | 3.3 NM | 6 NM | GP 3.00° TCH 43 |
| CATEGORY | A | B | C | D |
| LPV DA | 1566-¾ 250 (300-¾) | | | |
| LNAV/VNAV DA | 1630-⅞ 314 (400-⅞) | | | |
| LNAV MDA | 1700-1 | 384 (400-1) | 1700-1½ | 384 (400-1½) |
| C CIRCLING | 1760-1 444 (500-1) | 1900-1 584 (600-1) | 1900-1½ 584 (600-1½) | 2060-2½ 744 (800-2½) |

MONETT, MISSOURI
Orig 03NOV22

36°54'N-94°01'W

MONETT RGNL (HFJ)

RNAV (GPS) RWY 18

NC-3, 10 JUL 2025 to 07 AUG 2025

NC-3, 10 JUL 2025 to 07 AUG 2025