

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Inop table does not apply.

ALSF-2

MISSED APPROACH: Climb to 800, then climbing left turn to 2500 direct EARTH and hold.

| | | |
|-----------------------------------|-------------------------------------|-------------------|
| ORLANDO APP CON 134.95 281.425 | NASA TOWER ★ 128.55 (CTAF) 284.0 | GND CON 121.75 |
|-----------------------------------|-------------------------------------|-------------------|

ROCIT

2500

GP 3.00°

TCH 55

STARS

1500

RW15

1500

155°

1500

1500

6.1 NM

3.6 NM

0.9 NM

800

2500

EARTH

*0.9 NM to RW15

*LNAV only

| CATEGORY | A | B | C | D | E |
|--------------|----------------------|----------------------|-------------------------|-------|--------------|
| LPV DA | | 208-1 | 200 (200-1) | | |
| LNAV/VNAV DA | | 286-1 | 278 (300-1) | | |
| LNAV MDA | | 360-1 | 352 (400-1) | | |
| CIRCLING | 420-1 411 (500-1) | 460-1 451 (500-1) | 940-2¾ 931 (1000-2¾) | 940-3 | 931 (1000-3) |

TITUSVILLE, FLORIDA

Amdt 1A 25MAY17

SPACE FLORIDA LAUNCH AND LANDING FACILITY (TTS)

28°37'N-80°42'W

RNAV (GPS) RWY 15