

WAAS CH <b>82228</b> <b>W08A</b>	APP CRS <b>082°</b>	Rwy Idg <b>12000</b> TDZE <b>5354</b> Apt Elev <b>5434</b>
--	------------------------	--

RNAV (GPS) Y RWY 8

DENVER INTL (DEN)

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C (-13°F) or above 47°C (117°F). Simultaneous approach authorized with Rwy 7.  
DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations. For inoperative MALSR, increase LNAV Cat C/D visibility to RVR 5500.  
# RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 10000 direct KVERN and on track 041° to WITNE and hold.

D-ATIS <b>125.6 379.9</b> (ARR) <b>134.025</b> (DEP)	DENVER APP CON <b>119.3 307.3</b> (N) <b>120.35 379.3</b> (S)	DENVER TOWER <b>132.35 239.275</b>	GND CON <b>121.35 379.175</b> (W) <b>121.85 377.1</b> (E)	CLNC DEL <b>118.75</b>	CPDLC
--	---	---------------------------------------	---	---------------------------	-------

MISSED APCH FIX

(IF) LIPPS

7000

082°

(10)

(FAF) OWNER

RW08

5462

KVERN

041°

(11.2)

MSA RW08 25 NM

9700

6083

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).

LIPPS

10000

082°

OWNER

7000

7000

RW08

0.9 NM to RW08

\*LNAV only

WITNE

tr 041°

KVERN

10000

GP 3.00°

TCH 52

10 NM

4.1 NM

0.9 NM

CATEGORY	A	B	C	D
LPV DA #	5554/24		200 (200-½)	
LNAV/VNAV DA	5833/60		479 (400-1¼)	
LNAV MDA	5720/24 366 (300-½)		5720/35 366 (300-⅝)	

ELEV 5434

TDZE 5354

RADAR REQUIRED

HIRL all Rwys

TDZ/CL Rwys 7, 16L, 16R, 17R, 26, 34L, 34R, 35L, 35R

DENVER, COLORADO  
Amdt 1C 07DEC17

39°52'N-104°40'W

DENVER INTL (DEN)

RNAV (GPS) Y RWY 8

SW-1, 10 JUL 2025 to 07 AUG 2025

SW-1, 10 JUL 2025 to 07 AUG 2025