

LOC I-TVRRWY Idg5002

109.7

APP CRS

357°

TDZE

86

Apt Elev

86

ILS or LOC RWY 36

VICKSBURG TALLULAH RGNL (TVR)

RNP APCH - GPS required for procedure entry at BARNE.

ADF required.

For inop ALS when using Vicksburg Muni, MS altimeter setting, increase S-LOC Cats C and D visibility to 1 3/8 SM. When local altimeter setting not received, use Vicksburg Muni, MS altimeter setting: increase SHLS 36 DA to 309 feet; increase all MDAs 40 feet and visibility S-LOC 36 Cats C/D 1/8 SM and Circling Cats C/D 1/4 SM.

SSALR

MISSED APPROACH: Climb to 1200 then climbing left turn to 2100 direct TKH NDB and hold.

ASOS118.525	MEMPHIS CENTER132.5 259.1	UNICOM123.0 (CTAF)
-------------	---------------------------	--------------------

ELEV 86	D	TDZE 86
---------	---	---------

REIL Rwy 18

MIRL Rwy 18-36

FAF to MAP 6 NM

Knots	60	90	120	150	180
Min:Sec	6:00	4:00	3:00	2:24	2:00

1200	2100	TKH	TKH NDB	One Minute Holding Pattern
1200	2100	TKH	2061	177° → 4500
1200	2100	TKH	2100	357° → 2100
1200	2100	TKH	2100	GS 3.00° TCH 49
1200	2100	TKH	2100	6 NM
CATEGORY	A	B	C	D
S-ILS 36	286-1/2	200 (200-1/2)		
S-LOC 36	540-1/2	454 (500-1/2)	540-7/8	454 (500-7/8)
CIRCLING	540-1	454 (500-1)	720-1 3/4 634 (700-1 3/4)	720-2 634 (700-2)

TALLULAH, LOUISIANA

Amdt 1 05OCT23

32°21'N-91°02'W

VICKSBURG TALLULAH RGNL (TVR)

ILS or LOC RWY 36