

WAAS CH 45728 W27A	APP CRS 272°	Rwy Idg TDZE 1487 Apt Elev 1487
--	------------------------	---

RNAV (GPS) RWY 27

TOMAHAWK RGNL (TKV)


▼

▲

Rwy 27 helicopter visibility reduction below $\frac{3}{4}$ SM NA. DME/DME RNP-0.3 NA.
When local altimeter setting not received, use Rhinelander altimeter setting:
increase all MDA 60 feet and visibility LP Cat C and D $\frac{1}{8}$ SM and
LNAV Cat C and D and Circling Cat D $\frac{1}{4}$ SM.

MISSED APPROACH:
Climb to 4000 direct
YELUD and hold.

AWOS-3 118.250	MINNEAPOLIS CENTER 133.65 281.5	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------



ELEV 1487

TDZE 1487

4000

YELUD

3100

AXOVE

2380

YULUK

272°

to RWY 27

VGSI and descent angles not coincident
(VGSI Angle 3.00/TCH 27).

4401 X 75

0.4 % UP

272°

to RWY 27

CATEGORY	A	B	C	D
LP MDA	1840-1 353 (400-1)			
LNAV MDA	1860-1 373 (400-1)			
CIRCLING	1920-1 433 (500-1)	2020-1 533 (600-1)	2020-1½ 533 (600-1½)	2320-2¾ 833 (900-2¾)