

| | | |
|--|------------------------|---|
| WAAS CH 58221 W35A | APP CRS 348° | Rwy Ldg TDZE 5022 Apt Elev 5022 |
|--|------------------------|---|

RNAV (GPS) RWY 35
NEPHI MUNI (U14)

| | | |
|-----------------|--|--|
| RNP APCH - GPS. | Baro-VNAV NA when using Provo altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -24°C or above 12°C. Circling NA for Cat C east of Rwy 17 and 35. Rwy 35 helicopter visibility reduction below ¾ SM NA. VDP NA with Provo altimeter setting. When local altimeter setting not received, use Provo altimeter setting: increase LPV DA to 5416 feet and visibility all Cats ½ SM; increase LNAV/VNAV DA to 5740 feet and visibility all Cats ½ SM; increase all MDAs 160 feet and LNAV visibility Cats B/C/D and Circling visibility Cats A/B ½ SM. | MISSED APPROACH: Climb to 8200 then climbing left turn to 10600 direct PILTE and hold. |
|-----------------|--|--|

| | | |
|--------------------------|--|-----------------------------------|
| AWOS-3 118.275 | SALT LAKE CENTER 127.825 239.025 | UNICOM 123.075 (CTAF) 0 |
|--------------------------|--|-----------------------------------|

