

WAAS CH 45814 W16A	APP CRS 165°	Rwy Idg TDZE Apt Elev	4798 3086 3086
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 16

RONAN (7SØ)

RNP APCH.

▼

▲

NA

Baro-VNAV NA when using Missoula altimeter setting. For uncompensated Baro-VNAV systems, procedure NA below -21°C or above 54°C. Circling NA east of Rwy 16-34. When local altimeter setting not received, use Missoula altimeter setting: increase LPV DA to 3550 and LNAV/VNAV DA to 3639 and all visibilities ¼ SM; increase all MDAs 120 feet and LNAV Cat B and Circling Cats A and B visibility ¼ SM.

MISSED APPROACH:
Climb to 13000 direct IBBOR and on track 255° to HANIM and hold, continue climb-in-hold to 13000.

AWOS-3
119.925

SALT LAKE CITY CENTER
127.075 244.875

AUNICOM
122.8 (CTAF) Ø

Procedure NA for arrivals at ANGIL on V231 northbound.

Procedure NA for arrivals at HANIM on V120 westbound.

MSA RW16 2.5 NM

ELEV 3086

TDZE 3086

165°

91

4798 X 7.5

34

EGOCY

FATMI

GEDKE

IBBOR

HANIM

13000

IBBOR

tr 255°

HANIM

GP 3.00°
TCH 40

6700

5600

*4400

RW16

6.7 NM

3.8 NM

4 NM

*LNAV only

CATEGORY	A	B	C	D
LPV DA	3443-1¼	357 (400-1¼)	NA	NA
LNAV/VNAV DA	3532-1⅜	446 (500-1⅜)	NA	NA
LNAV MDA	3800-1	714 (800-1)	NA	NA
CIRCLING	3800-1	714 (800-1)	NA	NA

MIRL Rwy 16-34 Ø