


WAAS CH 93632 W10A	APP CRS 100°	Rwy Idg TDZE 928 Apt Elev 928
--	------------------------	---

RNAV (GPS) RWY 10



BOGGS FLD (USW)

RNP APCH.	<p>⚠ Circling Rwy 28 NA at night. Baro-VNAV and VDP NA when using Charleston altimeter setting. Rwy 10 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Charleston altimeter setting, increase LPV DA to 1247 feet, LNAV/VNAV DA to 1730 feet, and LNAV/VNAV visibility all Cats by $\frac{1}{2}$ SM; increase all MDAs 80 feet and LNAV visibility Cat B $\frac{1}{4}$ SM and Cat C and D $\frac{1}{2}$ SM, and Circling visibility Cats C and D by $\frac{1}{4}$ SM.</p>	MISSED APPROACH: Climb to 3200 direct RAPGE and hold.
-----------	---	---

AWOS-3 118.575	CHARLESTON APP CON 124.1 269.125	UNICOM 122.725 (CTAF) 0
--------------------------	--	-----------------------------------



ELEV 928	TDZE 928
----------	----------



CATEGORY	A	B	C	D
LPV DA		1178-1	250 (300-1)	
LNAV/VNAV DA		1661-2	733 (800-2)	
LNAV MDA	1620-1	692 (700-1)	1620-2	692 (700-2)
CIRCLING	1620-1 692 (700-1)	1760-1 $\frac{1}{4}$ 832 (900-1 $\frac{1}{4}$)	1760-2 $\frac{1}{2}$ 832 (900-2 $\frac{1}{2}$)	1760-2 $\frac{3}{4}$ 832 (900-2 $\frac{3}{4}$)

MIRL Rwy 10-28 0