

WAAS CH 62840 W17A	APP CRS 171°	Rwy Idg TDZE 693 Apt Elev 693	5943
--	------------------------	---	-------------

RNAV (GPS) RWY 17

KENNETH COPELAND (4T2)

RNP APCH.

NA

Baro-VNAV and VDP NA when using Fort Worth Meacham Intl altimeter setting. Rwy 17 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Obtain local altimeter setting on CTAF; when not received, use Fort Worth Meacham Intl altimeter setting: Increase LPV DA to 973 feet; increase LNAV/VNAV DA to 1135 feet; increase all MDA 40 feet and LNAV Cat C/D and Circling Cat C visibility $\frac{1}{4}$ SM.

MISSED APPROACH: Climb to 1200 then climbing right turn to 3100 direct ODGOY and hold.

LONE STAR APP CON 125.8 257.95	UNICOM 123.075 (CTAF) 0
--	-----------------------------------

ODGOY	3000	171°	ZEBAY	2400	CAPUV	2.7 NM to RW17	1200	3100	ODGOY
GP 3.00°	2400	*1580	*1.5 NM to RW17	RW17	*LNAV only.				
TCH 40	7 NM	2.6 NM	1.2 NM	1.5 NM					
CATEGORY	A	B	C	D					
LPV DA		943-1	250 (300-1)						
LNAV/VNAV DA		1105-1 $\frac{3}{8}$	412 (500-1 $\frac{3}{8}$)						
LNAV MDA	1200-1	507 (600-1)	1200-1 $\frac{3}{8}$	507 (600-1 $\frac{3}{8}$)					
CIRCLING	1240-1	547 (600-1)	1340-1 $\frac{3}{4}$	747 (800-2 $\frac{1}{2}$)					

FORT WORTH, TEXAS

Orig-A 21MAY20

32°59'N-97°30'W

KENNETH COPELAND (4T2)

RNAV (GPS) RWY 17