

WAAS CH 81835 W03A	APP CRS 034°	Rwy Ldg TDZE Apt Elev 7504 3295 3295
--	------------------------	--

RNAV (GPS) RWY 3

CAVERN CITY AIR TRML (CNM)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -10°C (14°F) or above 52°C (126°F). DME/DME RNP-0.3 NA. For inop MALSR, increase LNAV Cat C/D visibility to 2½ miles, and increase LNAV/VNAV all Cats visibility to ¾ mile.

MALSR

MISSED APPROACH: Climb to 5600 direct KEREY and hold.

ASOS 118.375	ALBUQUERQUE CENTER 135.875 292.15	UNICOM 123.0 (CTAF) 0
------------------------	---	---------------------------------

The main chart displays the RNAV (GPS) RWY 3 approach. Key features include:

- Waypoints:** AXEPE (IAF), WAMVA (IF), ZETVO (FAF), OXYAC, and KEREY.
- Altitudes:** 4670, 4940, 5600, 3339, and 3596.
- Angles:** 019°, 034°, 036°, 340°, and 214°.
- Distances:** 4 NM, 3.1 NM, 1.6 NM, and 2.4 NM.
- Obstacles:** 4670, 4940, 3596, and 3339.
- Missed Approach:** Climb to 5600 direct KEREY and hold.
- MSA:** MSA RW03 25 NM with a 8100 ft MSL.

Procedure NA for arrivals at AXEPE on V102 southwest bound.

Procedure NA for arrivals at LANIC on V560 southwest bound.

ELEV 3295 **D** TDZE 3295

WAMVA		ZETVO		OXYAC 4 NM to RW03		5600 KEREY	
6600		5600		*4600		*2.4 NM to RW03	
019°		034°		*LNAV only.		RW03	
GP 3.00°		TCH 51		4 NM		3.1 NM	
CATEGORY		A		B		C	
LPV DA		3495-½		200 (200-½)			
LNAV/VNAV DA		3545-½		250 (300-½)			
LNAV MDA		4100-½ 805 (900-½)		4100-¾ 805 (900-¾)		4100-1⅞ 805 (900-1⅞)	
CIRCLING		4100-1 805 (900-1)		4100-1¼ 805 (900-1¼)		4100-2½ 805 (900-2½)	
						4260-3 965 (1000-3)	

The inset chart shows the missed approach procedure and other details:

- Missed Approach:** Climb to 5600 direct KEREY and hold.
- Obstacles:** 5334 X 75, 5337 X 100, 7854 X 150, and 322.
- Angles:** 034°, 036°, 214°, and 322°.
- Distances:** 0.6% UP, 0.6% UP, and 0.6% UP.

CARLSBAD, NEW MEXICO
Orig-A 05MAR15

32°20'N-104°16'W

CAVERN CITY AIR TRML (CNM)

RNAV (GPS) RWY 3

SW-1, 07 AUG 2025 to 04 SEP 2025

SW-1, 07 AUG 2025 to 04 SEP 2025