

WAAS CH <b>93519</b> <b>W15A</b>	APP CRS <b>154°</b>	Rwy Ldg TDZE Apt Elev	<b>9001</b> <b>43</b> <b>46</b>
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) Y RWY 15  
CHARLESTON AFB/INTL (CHS)

RNP APCH.



**T**  
**A** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C. For inop ALS, increase LNAV Cat C/D visibility to RVR 6000.


ALSF-2



**MISSED APPROACH:** Climb to 3000 direct SHRMP and hold.

D-ATIS 124.75	CHARLESTON APP CON 120.7 306.925	CHARLESTON TOWER 126.0 239.0	GND CON 121.9 348.6	CLNC DEL 127.325 291.65	CPDLC
------------------	-------------------------------------	---------------------------------	------------------------	----------------------------	-------



CATEGORY		A	B	C	D
LPV	DA	243/18 200 (200-½)			
LNAV/ VNAV	DA	375/26 332 (400-½ )			
LNAV	MDA	460/24	417 (500- ½)	460/40	417 (500- ¾)
 CIRCLING		540-1	494 (500-1)	540-1½ 494 (500-1½)	740-2¼ 694 (700-2¼)

