LONE STAR DEP CON
125.2 343.65 (Rwy 13L/R)
124.3 282.275 (Rwy 31L/R)
D-ATIS 120.15
CLNC DEL 127.9
CPDLC
GND CON 121.75 348.6
LOVE TOWER 123.7 239.3
RADAR and DME required.
TOP ALTITUDE: ALL RUNWAYS: ASSIGNED BY ATC
N
168°
333°
MAVERICK
113.1 TTT
Chan 78
WICHITA FALLS
112.7 SPS
Chan 74
CHILDRESS
117.0 CDS
Chan 117
PANHANDLE
116.6 PNH
Chan 113
TEXICO
112.2 TXO
Chan 59
LUBBOCK
109.2 LBB
Chan 29
CORONA
115.5 CNX
Chan 102
ABILENE
113.7 ABI
Chan 84
MILLSAP
117.7 MQP
Chan 124
SCABI
FERRA
CEOLA
KIRST
PODDE
R-233
R-127
R-118
R-124
R-088
R-102
R-022
R-071
R-081
V114
V62
V66
129
4000 *2400 285° (37)
4000 *2500 264° (35)
250° 3500 *2800 (36)
14000 *3000 285° (92)
1400 *3200 307° (61)
5300 297° (87)
5900 305° (66)
FL180 *9300 272° (192)
FL180 *4700 282° (127)
FL180 *3500 264° (94)
3000 *2800 261° (113)
3700 253° (96)
WSATT 25 NM
2700
3600
090°
270°
NOTE: Chart not to scale.
TAKEOFF MINIMUMS
Rwys 31L/R: Standard.
Rwy 13L: Standard with minimum climb of 290'/NM to 1700.
Rwy 13R: Standard with minimum climb of 315'/NM to 1700.
NOTE: PODDE Transition: ATC assigned.
NOTE: JETS: Expect WORTH DEPARTURE.
NOTE: Props departing DAL must contact clearance delivery for departure instructions.
(CONTINUED ON FOLLOWING PAGE)