

ILS or LOC RWY 23R

LOC I-FFO 109.7	APCH CRS 233°	Rwy Idg 12,600 THRE 823 Arpt Elev 823
---------------------------	-------------------------	---

[USAF]

WRIGHT-PATTERSON AFB (KFFO)

DME or RADAR required for Localizer.

- ▼ *When ALS inop, increase RVR to 40 and vis to ¾ mile.
**When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile,
CAT CDE vis to 1¾ miles.

ALS-F-1



† MISSED APPROACH: Climb via FFO R-233 to 2000, at 3 DME turn left direct CLACK to 3000 and hold.

ATIS 124.475 269.9	COLUMBUS APP CON 118.85 269.275	PATTERSON TOWER 127.8 281.45	GND CON 121.8 335.8
------------------------------	---	--	-------------------------------

*** When Rwy 23R VGSi inop, circling to Rwy 23R NA at night.

† Missed approach requires use of RNAV or ATC radar monitoring.

Autocoupled approach NA below 1458' MSL.


1290



PATTERSON
Chan 29 FFO

LOCALIZER 109.7
I-FFO

2049



AKATE
3

1467



1299



1219



985



925



1024



1096



1033



1024



1096



1033



1024



1096



1033



1024



1096



1033



1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024

1096

1033

1024