

NDB DXB

385

APP CRS

354°

Rwy Idg

5494

TDZE

197

Apt Elev

202

NDB RWY 36

BEAUREGARD RGNL (DRI)

▼

NA

Inoperative table does not apply. Visibility reduction by helicopters NA. When local altimeter setting not received, use Fort Polk altimeter setting and increase all MDAs 60 feet and S-36 visibility Cat D ½ SM and Circling Cats C/D ¼ SM.

ODALS

MISSED APPROACH: Climb to 1000 then climbing left turn to 1700 direct DXB NDB and hold.

AWOS-3PT	POLK APP CON	UNICOM
118.225	123.7 261.3	122.8 (CTAF) 0

ELEV 202

TDZE 197

1000	1700	DXB	DXB NDB	One Minute Holding Pattern
VGSi and descent angles not coincident (VGSi Angle 3.00/TCH 50).				
4.2 NM				
CATEGORY	A	B	C	D
S-36	700-1	503 (500-1)	700-1½	503 (500-1½)
CIRCLING	720-1	518 (600-1)	780-1½	1000-2½
			578 (600-1½)	798 (800-2½)

DE RIDDER, LOUISIANA

Amtd 5B 04NOV21

30°50'N-93°20'W

BEAUREGARD RGNL (DRI)

NDB RWY 36

SC-4, 07 AUG 2025 to 04 SEP 2025

SC-4, 07 AUG 2025 to 04 SEP 2025