

| | | | |
|------------|---------|----------|------|
| VORTAC ELP | APP CRS | Rwy Ldg | 9025 |
| 115.2 | 245° | TDZE | 3962 |
| Chan 99 | | Apt Elev | 3962 |

VOR RWY 26L

EL PASO INTL (ELP)

⚠

ASR

Inop table does not apply to S-26L and CINAG fix minimums S-26L. Circling NA for Cat D northwest of Rwy 4-22.

MALSR

MISSED APPROACH: Climb to 4500 then climbing left turn to 7100 on heading 050° and on ELP VORTAC R-081 to FEMOL INT/9 DME and hold.

| | | | | |
|-------------|-----------------|---------------|-------------|-------------|
| D-ATIS | EL PASO APP CON | EL PASO TOWER | GND CON | CLNC DEL |
| 120.0 254.3 | 124.25 298.85 | 118.3 239.275 | 121.9 348.6 | 125.0 379.1 |

Procedure NA for arrivals at WATEX on V94-611 northwest bound.

4500

7100

hdg 050°

ELP R-081

FEMOL INT

| CATEGORY | A | B | C | D | E |
|---|--------------------|--------------------|---|---|----|
| S-26L | 4480-1 518 (600-1) | | 4480-1 ³ / ₈ 518 (600-1 ³ / ₈) | | NA |
| CIRCLING | 4480-1 518 (600-1) | | 4480-1 ¹ / ₂ 518 (600-1 ¹ / ₂) | 4680-2 718 (800-2) | NA |
| CINAG FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED) | | | | | |
| S-26L | 4380-1 418 (500-1) | | 4380-1 ¹ / ₈ 418 (500-1 ¹ / ₈) | | NA |
| CIRCLING | 4420-1 458 (500-1) | 4440-1 478 (500-1) | 4480-1 ¹ / ₂ 518 (600-1 ¹ / ₂) | 4680-2 ¹ / ₄ 718 (800-2 ¹ / ₄) | NA |

ELEV 3962 TDZE 3962

MIRL Rwy 8L-26R

REIL Rws 4 and 8R

HIRL Rws 4-22 and 8R-26L

| | | | | | |
|-------------------|------|------|------|------|------|
| FAF to MAP 3.8 NM | | | | | |
| Knots | 60 | 90 | 120 | 150 | 180 |
| Min:Sec | 3:48 | 2:32 | 1:54 | 1:31 | 1:16 |

EL PASO, TEXAS

Amdt 32D 20APR23

31°48'N-106°23'W

EL PASO INTL (ELP)

VOR RWY 26L