

HI-ILS Y or LOC Y RWY 35L

LOC I-EFD 111.1 APCH CRS 354° Rwy Idg 9001
 TDZE 28 [USAF] ELLINGTON (KEFD)

DME required. RADAR required for procedure entry.

▲ * When ALS inop, increase CAT CDE RVR to 60.
 ** Circling not authorized W of rwy 17L-35R

ATIS 135.575 269.9 HOUSTON APP CON 134.45 284.0 TOWER 126.05 253.5 GND CON 121.6 275.8

ELLINGTON
 Chan 31 EFD

LOCALIZER 111.1
 I-EFD

TRINITY
 114.75 MHF
 Chan 94(Y)

DME from EFD TACAN, simultaneous reception of I-EFD and EFD DME required.

EMERG SAFE ALT 100 NM 16,000

500 3100 WATFO EFD 16
 EFD R-136

TACAN JUVUM EFD 2.3 BAYUU EFD 1.4 620

0.6 NM 1.1 NM 4.6 NM

CATEGORY C D E

S-ILS 35L 228/40 200 (200-34)

S-LOC 35L * 440/50 412 (500-1)

**
 C CIRCLING 580-1½ (600-1½) 640-2 (700-2) 700-2¼ (700-2¼)

547 (600-1½) 607 (700-2) 667 (700-2¼)

ELEV 33 D TDZE 28

17R 17L 35L 35R

TWR 112

9001 x 130 4609 x 75 8001 x 150

HIRL Rwy 4-22 and 17R-35L
 TDZL/CL Rwy 17R, 22 and 35L

HOUSTON, TEXAS

29°36'N-95°10'W

ELLINGTON (KEFD)

HI-ILS Y or LOC Y RWY 35L

SC-5, 07 AUG 2025 to 04 SEP 2025

SC-5, 07 AUG 2025 to 04 SEP 2025