

LOC/DME I-HON

110.3

Chan 40

APP CRS

121°

Rwy Idg

7201

TDZE

1289

Apt Elev

1289

ILS or LOC RWY 12

HURON RGNL (HON)

RNAV 1-GPS or RADAR required for procedure entry. ADF required.
From HUMSO and WEDEM: RNAV-1 GPS required.

MALSR

MISSED APPROACH: Climb to 3000 then left turn direct BEADY LOM and hold.

ASOS

118.125

MINNEAPOLIS CENTER

126.25 339.8

UNICOM

123.0 (CTAF) 1

The diagram illustrates the ILS/LOC RWY 12 approach. Key features include:

- Initial Approach:** 3000 NoPT (7-2) at 211°.
- Intermediate Approach:** 3000 (7-1) at 121°.
- Final Approach:** 3000 (7-1) at 121°.
- Altitudes:** 1728 A, 1436 ± A, 1616 A.
- Navigation Aids:** (IAF) HUMSO, (IF) CELKU, (IF) WEDEM, (IAF) WEDEM, (IAF) WEDEM.
- Hold:** 6000 3000 HOLD.
- Localizer:** 110.3 I-HON Chan 40.
- MSA:** MSA HO 25 NM, 3400.

One Minute Holding Pattern

6000 3000

301° 121°

2997

3000

GS 3.00° TCH 50

3.7 NM

1.4 NM

3000

HO BEADY LOM I-HON 6.5

*I-HON 2.8

*LOC only I-HON 1.4

ELEV 1289 D TDZE 1289

HIRL Rwy 12-30 1

MIRL Rwy 18-36 1

REIL Rwy 18, 30 and 36 1

121°

81

5000 X 75

1354

36

7201 X 100

CATEGORY	A	B	C	D
S-ILS 12	1489-1/2 200 (200-1/2)			
S-LOC 12	1780-1/2 491 (500-1/2)		1780-1 491 (500-1)	
CIRCLING	1820-1 531 (600-1)		1920-1 3/4 631 (700-1 3/4)	1980-2 1/4 691 (700-2 1/4)

FAC TO MAP 5.1 NM

Knots	60	90	120	150	180
Min:Sec	5:06	3:24	2:33	2:02	1:42

HURON, SOUTH DAKOTA

Amdt 11 25FEB21

44°23'N-98°14'W

HURON RGNL (HON)

ILS or LOC RWY 12