


24361

INDIANAPOLIS INTL (IND)
INDIANAPOLIS, INDIANA

BRICKYARD
116.3 VHP 
Chan 110

LOCALIZER
111.75 I-UZK 
Chan 54(Y)

**TOP ALTITUDE:
ASSIGNED BY
ATC**


TERRE HAUTE
115.3 TTH ...
Chan 100

HOOSIER
110.2 OOM **===**
Chan 39

SNEVA
RADAR


FOOT RADAR

DAWNN
10000
(For LOUISVILLE Transition)

LOCALIZER
111.15 I-OQV 
Chan 48(Y)

LOCALIZER
111.15 I-FVJ
Chan 48(Y)

LOUISVILLE
114.8 IU ::
Chan 95

MYSTIC
108.2 MYS 

TAKEOFF MINIMUMS:

Rwys 5L/R, 14, 23L/R, 32: Standard.

NOTE: RADAR required.

NOTE: Select appropriate localizer/DME frequency/channel prior to departure.

NOTE: Turbojets accelerate to 250K until reaching 10000, if unable advise ATC.

NOTE: Assigned to aircraft with a requested altitude of 11000 or above.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

DAWNN ONE DEPARTURE
(DAWNN1.DAWNN) 07DEC17

INDIANAPOLIS, INDIANA
INDIANAPOLIS INTL (IND)

EC-2, 07 AUG 2025 to 04 SEP 2025