

APP CRS 320°	Rwy Ldg	7278
	TDZE	793
	Apt Elev	796

RNAV (RNP) Z RWY 32

INDIANAPOLIS INTL (IND)

▼

For uncompensated Baro-VNAV systems, procedure NA below -18°C (2°F) or above 54°C (130°F). GPS required.

MALSR

MISSED APPROACH: Climb to 3000 on track 320° to KEADY and hold.

D-ATIS 134.25	INDIANAPOLIS APP CON 128.175 317.8	INDY TOWER 120.9 251.1	GND CON 121.9	CLNC DEL 128.75 251.1	CPDLC
------------------	---------------------------------------	---------------------------	------------------	--------------------------	-------

The main chart displays the RNP Z RWY 32 procedure. Key features include:

- Initial Approach:** (IF) CRCL 6000 210K (RF REQD) at 4400 ft, 140° heading, 15.3 NM.
- Intermediate Approach:** (IF) HNKLE 5000 210K (RF REQD) at 3600 ft, 205° heading, 4.2 NM.
- Final Approach:** (FAF) BTTLR at 2400 ft, 320° heading, 4.9 NM.
- Missed Approach:** Climb to 3000 ft on track 320° to KEADY and hold.
- Obstacles:** HIKEK (3600 ft, 2.9 NM), EVAVE (200K, 4.2 NM), BDAWG (5000 ft, 4.2 NM), CUREG (200K, 4.6 NM), DLNGR (3600 ft, 12.9 NM).
- Navigation Aids:** MSA RW32 25 NM (3100 ft), (IF) PNFLD 6000 210K (RF REQD) at 4400 ft, 139° heading, 5.3 NM.
- Waypoints:** KEADY, RW32, BTTLR, CUREG, EVAVE, BDAWG, HIKEK, DLNGR, HNKLE, CRCL.

ELEV 796

D

TDZE 793

Vertical profile view showing altitude (ft) vs distance (NM). Key points include: 3000 ft at 0 NM, 2400 ft at 4.9 NM, 2000 ft at 10.0 NM, 1500 ft at 15.0 NM, 1000 ft at 20.0 NM, 500 ft at 25.0 NM. Obstacles are marked with their MSL and AGL altitudes.

HIRL all Rwys

TDZ/CL Rwys 5L and 5R

3000

↑

Ir 320°

KEADY

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).

BTTLR

2400

GP 3.00°

TCH 53

See planview for multiple IF locations.

4.9 NM

CATEGORY	A	B	C	D
RNP 0.19 DA		1134/30	341 (400-%)	
RNP 0.30 DA		1196/45	403 (400-%)	

AUTHORIZATION REQUIRED

INDIANAPOLIS, INDIANA

Amdt 2 10NOV16

39°43'N-86°18'W

INDIANAPOLIS INTL (IND)

RNAV (RNP) Z RWY 32