

LOC I-CRG	APP CRS	Rwy Ldg	4008
111.7	321°	TDZE	41
		Apt Elev	41

ILS or LOC RWY 32

JACKSONVILLE EXEC AT CRAIG (CRG)

⚠

Night landing: Rwy 5 NA. DME or radar required. Helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Jacksonville Intl altimeter setting: increase DA to 273 feet; increase all MDAs 40 feet and Circling visibility Cat C ¼ SM. For inop MALS, increase S-LOC 32 Cats C/D visibility to 1¼ mile. For inop MALS, when using Jacksonville Intl altimeter setting, increase S-LOC 32 Cats C/D visibility to 1¾ mile.

MALS

AS

⬆

MISSED APPROACH: Climb to 700 then climbing right turn to 1900 on heading 180° and on CRG VORTAC R-139 to JEVAG/CRG VORTAC 11.8 DME/RADAR and hold.

ATIS	JACKSONVILLE APP CON	CRAIG TOWER ★	GND CON	CLNC DEL	UNICOM
125.4	124.9 308.4	132.1 (CTAF) 269.525	121.8	118.35	122.95

LOCALIZER 111.7
I-CRG

CRAIG
114.5 CRG Chan 92

1900 to JEVAG
139° (11.8)

ADERR
CRG 5.8
RADAR

(IF/IAF)
JEVAG
CRG 11.8
RADAR

1900
321°

141°

141°

DME or RADAR REQUIRED

MSA CRG 25 NM
2100

ELEV	41	TDZE	41
------	----	------	----

MIRL Rwy 5-23

HIRL Rwy 14-32

REIL Rws 14 and 23

FAF to MAP 5.7 NM

Knots	60	90	120	150	180
Min:Sec	5:42	3:48	2:51	2:17	1:54

700	1900	CRG R-139	JEVAG CRG 11.8	ADERR CRG 5.8 RADAR	JEVAG CRG 11.8 RADAR	One Minute Holding Pattern
-----	------	-----------	----------------	---------------------	----------------------	----------------------------

1900

141°

141°

GS 3.00°
TCH 42

CATEGORY	A	B	C	D
S-ILS 32	241-1	200 (200-1)		
S-LOC 32	480-1	439 (500-1)		
CIRCLING	500-1 459 (500-1)	600-1 559 (600-1)	620-1½ 579 (600-1½)	800-2½ 759 (800-2½)

JACKSONVILLE, FLORIDA

Amdt 5B 30DEC21

JACKSONVILLE EXEC AT CRAIG (CRG)

ILS or LOC RWY 32

30°20'N-81°31'W

SE-3, 07 AUG 2025 to 04 SEP 2025

SE-3, 07 AUG 2025 to 04 SEP 2025