

WAAS CH 56509 W13A	APP CRS 135°	Rwy Idg 5310 TDZE 656 Apt Elev 656
--	------------------------	---

RNAV (GPS) RWY 13
LA CROSSE RGNL (LSE)

▼ Baro-VNAV NA when using Winona altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -27° C (-16° F) or above 54° C (130° F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below $\frac{3}{4}$ SM NA. Circling to Rwy 22 NA at night.

▲ -22°C When local altimeter setting not received, use Winona altimeter setting and increase DA 53 feet, increase LPV and LNAV/VNAV visibility $\frac{1}{4}$ mile all cats, increase all MDA 60 feet, increase LNAV Cats C/D and Circling Cat B visibility $\frac{1}{4}$ mile.

✳

MISSED APPROACH:
Climb to 3000 direct
COSUT and on track
117° to WEVBA
and hold.

ATIS 124.95	MINNEAPOLIS CENTER 128.6 363.0	LA CROSSE TOWER ★ 118.45 (CTAF) 0 251.075	GND CON 121.8	UNICOM 122.95
-----------------------	--	---	-------------------------	-------------------------

