

WAAS CH <b>87029</b> <b>W03A</b>	APP CRS <b>032°</b>	Rwy Idg TDZE <b>860</b> Apt Elev <b>887</b>	<b>6769</b> <b>860</b> <b>887</b>
--	------------------------	---	---


RNAV (GPS) RWY 3

DANE COUNTY RGNL/TRUAX FLD (MSN)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 3600 direct FONUV and hold.

ATIS <b>124.65 278.3</b>	MADISON APP CON ★ <b>135.45 343.7</b>	MADISON TOWER ★ <b>119.3 (CTAF) 0 257.8</b>	GND CON <b>121.9 348.6</b>	CLNC DEL <b>121.625</b>	UNICOM <b>122.95</b>
-----------------------------	--	--	-------------------------------	----------------------------	-------------------------



4 NM Holding Pattern		3600 FONUV	
WIROD		*LNAV only	
3600 ← 212°		032° →	
GP 3.00°		2700	
TCH 49		2600	
5 NM		3.3 NM	
CATEGORY		A	
LPV DA		1060-¾ 200 (200-¾)	
LNAV/VNAV DA		1179-1 319 (300-1)	
LNAV MDA		1320-1 460 (500-1)	
CIRCLING		1420-1 533 (600-1)	
		1460-1 573 (600-1)	
		1460-1½ 573 (600-1½)	
		1700-2¾ 813 (900-2¾)	

