


APP CRS <b>116°</b>	Rwy Ldg <b>10000</b> TDZE <b>9</b> Apt Elev <b>9</b>
------------------------	--

RNAV (RNP) Z RWY 12  
OAKLAND INTL (OAK)

RNP AR APCH.		<b>MALSR</b> 		<b>MISSED APPROACH:</b> Climb direct HISIS to cross HISIS at or below 1600 then climb to 5400 on track 116° to YICPU and on track 103° to DECOT and hold, continue climb-in-hold to 5400.			
<b>▼</b> For uncompensated Baro-VNAV systems, procedure NA below 0°C or above 54°C. For inop ALS increase RNP 0.15 visibility all Cats to RVR 4500, RNP 0.30 visibility all Cats to RVR 5500.							
<b>D-ATIS</b> <b>133.775</b>	<b>NORCAL APP CON</b> <b>125.35 263.15</b>	<b>OAKLAND TOWER</b> <b>118.3 291.65</b> (Rwys 10L/R-28L/R, 15-33) <b>127.2 256.9</b> (Rwy 12-30)		<b>GND CON</b> <b>121.9</b> (Rwys 10L/R-28L/R, 15-33) <b>121.75</b> (Rwy 12-30)		<b>CLNC DEL</b> <b>121.1</b>	<b>CPDLC</b>

