

WAAS

CH 81807

W36A

APP CRS

356°

Rwy Idg

7339

TDZE

1066

Apt Elev

1087

RNAV (GPS) RWY 36

NEW CENTURY AIRCENTER (IXD)

DME/DME RNP-0.3 NA. For inop MALS, increase LNAV Cat D visibility to 1¼ and LPV visibility to 1 all Cats. If local altimeter setting not received, use Johnson County Exec altimeter setting and increase all DA/MDAs 20 feet. VDP NA with Johnson County Exec altimeter setting.

MALS

MISSED APPROACH: Climb to 3100 direct ZODPU and hold.

ASOS 135.325	KANSAS CITY APP CON 118.9 251.075	NEW CENTURY TOWER ★ 133.0 (CTAF) 0	GND CON 124.3	UNICOM 122.95
-----------------	--------------------------------------	---------------------------------------	------------------	------------------

Λ 2048

30 NM to UNOXY

176°

3100

UNOXY

086°

30 NM to NAPVY

176°

3100

NAPVY

266°

356°

176°

5 NM

30 NM to ANQUM (NoPT)

086°

266°

3100

3100 NoPT (5) 086° (IAF) UNOXY

3100 NoPT (5) 266° (IAF) NAPVY

2700 (5) 356° (IF/IAF) ANQUM

1189± Λ

2700 (5) 356°

Λ 1196±

RW36

ELEV 1087

TDZE 1066

81

7339 X 150

5132 X 100

36

TWR 1147±

REIL Rwy 18 0

MIRL Rwy 4-22 0

HIRL Rwy 18-36 0

0.5% UP

356° to RW36

5 NM Holding Pattern

ANQUM

3100

176°

356°

GP 3.00° TCH 50

356°

2700

6 NM

3.9 NM

1.1 NM

3100

ZODPU

*LNAV only.

*1.1 NM to RW36

RW36

CATEGORY	A	B	C	D
LPV DA	1316-½ 250 (300-½)			
LNAV/VNAV DA	NA			
LNAV MDA	1440-½ 374 (400-½)		1440-1 374 (400-1)	
CIRCLING	1560-1 473 (500-1)		1580-1½ 493 (500-1½)	1640-2 553 (600-2)

Olathe, Kansas

Amdt 2A 30JAN20

38°50'N-94°53'W

NEW CENTURY AIRCENTER (IXD)

RNAV (GPS) RWY 36

NC-2, 07 AUG 2025 to 04 SEP 2025

NC-2, 07 AUG 2025 to 04 SEP 2025