

LOC/DME I-PPY 110.9 Chan 46	APP CRS 178°	Rwy Ldg 8013 TDZE 982 Apt Elev 985
---	------------------------	---

ILS or LOC RWY 18

RADAR required for procedure entry. DME required for LOC only.


MALSR

MISSED APPROACH: Climb to 1800 then climbing left turn to 3000 direct OVR VORTAC and hold.

RVR 1800 authorized with use of FD or AP or HUD to DA.



D-ATIS 120.4	OMAHA APP CON 135.875 354.05	OMAHA TOWER 132.1 256.9	GND CON 121.9	CLNC DEL 119.9
------------------------	--	-----------------------------------	-------------------------	--------------------------



1800 ↑	3000 ↘	OV R ↓				
* LOC only			I-PPY 1.5 I-PPY 2.4 PINNO I-PPY (3) CEPUT I-PPY (7) TASKY I-PPY (13) GS 3.00° TCH 52			
CATEGORY	A	B	C	D		
S-ILS 18 #	1182/24 200 (200-½)					
S-LOC 18	1320/24	338 (400-½)	1320/26	338 (400-½)		
CIRCLING	1660-1 675 (700-1)	1680-1 695 (700-1)	2000-3 1015 (1100-3)	2040-3 1055 (1100-3)		