

WAAS CH 90122	APP CRS 268°	Rwy Idg TDZE 11	8864
W27B		Apt Elev 36	

RNAV (GPS) RWY 27R
PHILADELPHIA INTL (PHL)

<div><div><div>▼</div><div>▲</div></div><div>For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C (11°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop ALS, increase LNAV/VNAV all Cats visibility to 1½ SM and LNAV Cat C/D to 2 SM.</div></div>			<div>MALSR</div> <div><div>AS</div><div><div></div><div></div><div></div><div></div><div></div><div></div></div></div>	MISSED APPROACH: Climb to 3000 direct LANDI and on track 294° to MXE VORTAC and hold.
<div>D-ATIS</div> <div>ARR 133.4</div> <div>DEP 135.925</div>	<div>PHILADELPHIA APP CON</div> <div>124.35 319.15</div>	<div>PHILADELPHIA TOWER</div> <div>118.5 327.05 (Rwys 9L/27R, 8/26 and 17/35)</div> <div>135.1 327.05 (Rwy 9R/27L)</div>	<div>GND CON</div> <div>121.9 348.6</div>	<div>CLNC DEL</div> <div>118.85 348.6</div>

