

WAAS  
CH 53404  
W13A

APP CRS  
133°

Rwy Idg  
TDZE 6900  
1731  
Apt Elev 1744

RNAV (GPS) RWY 13  
PIERRE RGNL (PIR)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 45°C (113°F).  
DME/DME RNP-0,3 NA.

MISSED APPROACH: Climb to 4000 direct HOGEX and hold.

ASOS 119.025	MINNEAPOLIS CENTER 125.1 269.1	CTAF 122.70	UNICOM 122.95
-----------------	-----------------------------------	----------------	------------------

ELEV 1744

TDZE 1731

REIL Rwy 7, 13, and 25

HIRL Rwy 7-25 and 13-31

4 NM Holding Pattern	FASIP	HEDGO	BATPE 2 NM to RW13	HOGEX
4000	313°	133°	133°	4000
GP 3.00° TCH 52	3500	2400	1.4 NM to RW13	RW13
6.1 NM	3.3 NM	0.6	1.4 NM	
CATEGORY	A	B	C	D
LPV DA	1981-¾ 250 (300-¾)			
LNAV/VNAV DA	2285-2 554 (600-2)			
LNAV MDA	2220-1 489 (500-1)	2220-1½ 489 (500-1½)	2220-1½ 489 (500-1½)	2220-1½ 489 (500-1½)
CIRCLING	2240-1 496 (500-1)	2300-1 556 (600-1)	2400-1¾ 656 (700-1¾)	2460-2¼ 716 (800-2¼)

PIERRE, SOUTH DAKOTA

Amcl 2A 08OCT20

44°23'N-100°17'W

PIERRE RGNL (PIR)

RNAV (GPS) RWY 13