

WAAS CH 82514 W23A	APP CRS 226°	Rwy Ldg TDZE Apt Elev	7031 3067 3080
--	------------------------	-----------------------------	---

RNAV (GPS) Y RWY 23

ROBERTS FLD (RDM)

⚠

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 53°C (128°F).
DME/DME RNP-0.3 NA. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM and LNAV Cat C/D visibility to 1 SM.

MALSR

MISSED APPROACH: Climb to 8500 direct WELPU and on track 138° to URBIA and hold, continue climb-in-hold to 8500.

ATIS 119.025	SEATTLE CENTER 126.15 269.475	REDMOND TOWER★ 124.5 (CTAF) 0 256.8	GND CON 121.8	UNICOM 122.95
------------------------	---	---	-------------------------	-------------------------

ELEV 3080	D	TDZE 3067	8500	WELPU	tr 138°	URBIA	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 51).			
			*LNAV only			ARUBE 2.2 NM to RW23	VERNN 5100	HUTKI 5800	YUBUB 6600	GP 3.00° TCH 47
			*1.1 NM to RW23			1.1 NM	1.1 NM	4.1 NM	4.4 NM	4.7 NM
			CATEGORY	A		B		C		D
			LPV DA	3267-½		200 (200-½)				
			LNAV/VNAV DA	3383-⅝		316 (400-⅝)				
			LNAV MDA	3440-½		373 (400-½)		3440-¾		373 (400-¾)
			CIRCLING	3540-1		460 (500-1)		3560-1		480 (500-1)
				3640-1½		560 (600-1½)		3760-2¼		680 (700-2¼)

REDMOND, OREGON

Amtd 1A 01FEB18

44°15'N-121°09'W

ROBERTS FLD (RDM)

RNAV (GPS) Y RWY 23