

WAAS CH <b>69302</b> <b>W21A</b>	APP CRS <b>215°</b>	Rwy Ldg <b>13000</b> TDZE <b>3633</b> Apt Elev <b>3671</b>
--	------------------------	--

RNAV (GPS) RWY 21

ROSWell AIR CENTER (ROW)

RNP APCH-GPS.					<div>MALSR</div> <div><div><div>AS</div><div>⋮</div></div></div>	MISSED APPROACH: Climb to 6300 direct GICEC and hold.					
<div><div><div>▼</div><div>▲</div><div>ASR</div></div><div>For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 41°C. When local altimeter setting not received, use Artesia altimeter setting: increase LPV DA to 3979 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 4075 feet and all visibilities ½ SM; increase all MDAs 80 feet and LNAV Cat C/D visibility ½ SM and Circling Cat D visibility ¼ SM. Baro-VNAV and VDP NA when using Artesia altimeter setting. For inop ALS, increase LPV all Cats visibility to ¾ SM, and LNAV/VNAV all Cats visibility to 1 SM. For inop ALS when using Artesia altimeter setting, increase LPV all Cats visibility to 1 SM and LNAV/VNAV all Cats visibility to 1¾ SM.</div></div>											
ATIS 128.45 306.2		ROSWell APP CON ★ 119.6 239.0		ROSWell TOWER ★ 118.5(CTAF) 233.7		GND CON 121.9 348.6		CLNC DEL 132.875 282.25		UNICOM 122.95	

