

25219

ILS or LOC RWY 12R
ST LOUIS LAMBERT INTL (STL)

MISSED APPROACH: Climb to 5000 on STL VORTAC R-128 to FONTI INT/STL 22.4 DME and hold, continue climb-in-hold to 5000.

4500 to PAULY
078° hdg (2.1) and
123° (1.7) (IF)

PAULY INT
17.8
RADAR

NAIKIN INT
12.5
RADAR

ST. LOUIS
117.4 STL 25 NM
Chan 121

TUDNE INT
7.6
RADAR

110.8 FTZ
R-045
Chan 45

110.8 FTZ
R-059
Chan 45

Procedure NA for arrivals at
SADEN on V4 westbound.

697±

714±

LOCALIZER 109.7
I-LMR
Chan 34

ALTERNATE MISSED APCH FIX

TROY
116.0
Chan 107

FONTI INT
STL 22.4

MSA STL 25 NM
2300
2800

090° to 270°

ELEV 617

TDZE 12R 540
TDZE 12L 541

Rwy 6-24 7603 X 150
Rwy 13-20 0000 X 150

PAULY INT I-LMR 17.8
NAIRN INT I-LMR 12.5
TUDNE INT I-LMR 7.6
I-LMR 3
I-LMR 1.9

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 71).

5000
STL R-128
FONTE INT

4500
123°
3600
2400
2400
5.3 NM
4.9 NM
4.6 NM
1.2 NM

GS 3.00°
TCH 54

CATEGORY	A	B	C	D	E
S-ILS 12R	740/18 200 (200-½)				
S-LOC 12R	960/40 420 (400-¾)				
SIDESTEP 12L	980-1 439 (400-1)	980-1½ 439 (400-1½)		980-2 439 (400-2)	

ST LOUIS LAMBERT INTL (STL)
ILS or LOC RWY 12R

NC-3, 07 AUG 2025 to 04 SEP 2025