

D-ATIS  
124.75 125.625  
CLNC DEL  
127.3 379.975  
CPDLC  
SALT LAKE CITY DEP CON  
128.6 322.3

TAKEOFF MINIMUMS

Rwys 14, 32, 34L/R, 35: NA- ATC.  
Rwys 16L/R, 17: Assigned heading 160°, standard with minimum climb of 260' per NM to 6000; assigned heading 280° CW 340°, standard with minimum climb of 400' per NM to 8300.

- NOTE: DME required.
- NOTE: RADAR required.
- NOTE: This is a RADAR vector departure to assigned route or fix.

TOP ALTITUDE:  
10000

WASATCH  
116.8 TCH  
Chan 115

FAIRFIELD  
116.6 FFU  
Chan 113

DELTA  
116.1 DTA  
Chan 108

MILFORD  
112.1 MLF  
Chan 58

TONOPAH  
116.0 TPH  
Chan 107

HANKSVILLE  
115.9 HVE  
Chan 106

COALDALE  
117.7 OAL  
Chan 124

WILSON CREEK  
116.3 ILC  
Chan 110

BRYCE CANYON  
112.8 BCE  
Chan 75

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

SW-4, 07 AUG 2025 to 04 SEP 2025

SW-4, 07 AUG 2025 to 04 SEP 2025