

WAAS
CH **99502**
W20A

APP CRS
196°

Rwy Idg
TDZE **54**
Apt Elev **56**

RNAV (GPS) Y RWY 20R

JOHN WAYNE/ORANGE COUNTY (SNA)

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 5°C or above 54°C. Circling Rwy 20L NA at night. For inop ALS increase LNAV/VNAV visibility to 1 ½ SM.
*RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 3000 direct MINOE.

D-ATIS 126.0	SOCAL APP CON 121.3 263.1	JOHN WAYNE TOWER ★ 126.8 (CTAF) 343.625	GND CON 120.8	CLNC DEL 118.0	CPDLC	UNICOM 122.95
------------------------	-------------------------------------	---	-------------------------	--------------------------	-------	-------------------------

ELEV 56	D	TDZE 54
REIL Rwy 20L MIRL Rwy 2R-20L HIRL Rwy 2L-20R		
VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 68).		
MINOE 3000		
VEGYU 4.2 NM to RW20R		
LEMON 6.6 NM to RW20R		
HUKEM 2900		
SAGER 3500		
GP 3.00° TCH 51		
CATEGORY	A	B
LPV DA*	255/24	201 (200-½)
LNAV/VNAV DA	516/50	462 (500-1)
LNAV MDA	580/24 526 (600-½)	580/55 526 (600-1)
C CIRCLING	640-1 584 (600-1)	840-2¼ 784 (800-2¼) 1180-3 1124 (1200-3)

SANTA ANA, CALIFORNIA

JOHN WAYNE/ORANGE COUNTY (SNA)

Amtd 4 26DEC24

33°41'N-117°52'W

RNAV (GPS) Y RWY 20R