

|  |                        |   |
|--|------------------------|---|
| WAAS<br>CH <b>97518</b><br><b>W25A</b> | APP CRS<br><b>256°</b> | Rwy Ldg <b>6248</b><br>TDZE <b>5507</b><br>Apt Elev <b>5507</b> |
|--|------------------------|---|

RNAV (GPS) RWY 25  
FOUR CORNERS RGNL (FMN)

RNP APCH-GPS.

**T** Baro-VNAV and VDP NA when using Durango altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Circling NA for Cat D southeast of Rwy 5 and south of Rwy 25. When local altimeter setting not received, use Durango altimeter setting and increase LPV DA to 5950 feet and all visibilities ½ SM. Increase LNAV/VNAV DA to 6312 feet and all visibilities ½ SM. Increase all MDAs 260 feet and LNAV visibilities Cat C/D ¾ SM, and Circling visibility Cat B ¼ SM and Cat C ½ SM.

**MISSED APPROACH:** Climb to 8000 direct HASIT and hold.

ATIS  
127.15

DENVER CENTER  
118,575 348.7

FARMINGTON TOWER★  
118.9 (CTAF) **L** 257.8

GND CON  
**121.7**

UNICOM  
122.95

MISSED APCH FIX

7151A



DURANGO  
DRO

Diagram illustrating the geometry of the HASIT instrument. The beam size is 76°, and the detector size is 256°. The distance from the source to the detector is 7 NM. The label HASIT is present.

6192

Aztec  
Muni

A7091

6040 ± Δ KODYS  
3.4 nm  
RW25

Δ 5611

RW25

(FAF  
EPOT

800

(IF)  
POME


400  
51°—



LY

Λ<sup>5980</sup>  
Λ<sup>6351</sup>

8400  
339°  
(15.1)



MSA RW 25 25 NM  
9700

|      |      |
|------|------|
| ELEV | 5507 |
|------|------|

**D**

TDZE 5507

|   |   |
|---|---|
| 8000  | HASIT   |
|  |  |

REIL Rwys 23 and 25 **L**  
MIRL Rwys 5-23 and 7-25 **L**

FARMINGTON, NEW MEXICO

Amdt 2 02DEC21

36°44'N-108°14'W

FOUR CORNERS RGNL (FMN)

RNAV (GPS) RWY 25

SW-1, 07 AUG 2025 to 04 SEP 2025

SW-1, 07 AUG 2025 to 04 SEP 2025